

LED Area Lighting



RoHS



Lifetime
L90 @
46,000 hrs






5 Year
Limited
Warranty



FEATURES

- Light Source: **PHILIPS**
- Power Supply: **MEAN WELL** **SOSEN**
- Dimmable: 0-10V, Photocell Sensor, Motion Sensor
- Type II-M, Type III-M, TYPE III-S, Type IV-S, Type V-M 90°X120°
- Robust Aluminium and Polycarbonate Casing
- CRI: >90
- Operating Temperature: -30°C to 50°C



PRODUCT FAMILY	POWER (Watts)	VOLTAGE (VAC)	LUMENS* (lm)	C.C.T. (Kelvin)	DLC VERSION	DLC CLASSIFICATION	MODEL NUMBER
NAL SERIES	80	100-277	10,800	3K, 4K, 5K, 5.7K	4.4	PREMIUM	AMINAL-WAC-80
		200-480					AMINAL-WAS-80
	100	100-277	13,500				AMINAL-WAC-100
		200-480					AMINAL-WAS-100
	150	100-277	20,250				AMINAL-WAC-150
		200-480					AMINAL-WAS-150
	185	100-277	24,050				AMINAL-WAC-185
		200-480					AMINAL-WAS-185
	240	100-277	32,400				AMINAL-WAC-240
		200-480					AMINAL-WAS-240
	300	100-277	40,500				AMINAL-WAC-300
		200-480					AMINAL-WAS-300
	400	100-277	52,000				AMINAL-WAC-400
		200-480					AMINAL-WAS-400

* Delivered Lumens